




Top View



Flat Top
8" - 4,000 lb
10" - 5,000 lb
12" - 6,000 lb
16" - 8,000 lb




Manhole Base Preformed Invert Detail



Riser Weights
12" - 18,50 lb
16" - 2,450 lb
24" - 3,650 lb
32" - 4,850 lb
36" - 5,450 lb
48" - 7,250 lb
60" - 9,050 lb
64" - 9,650 lb
72" - 10,900 lb

Custom Heights
Available in all pieces



Base Weights
12" - 5,850 lb
16" - 6,450 lb
24" - 7,650 lb
32" - 8,900 lb
36" - 9,500 lb
48" - 11,300 lb
60" - 13,100 lb
64" - 13,700 lb
72" - 14,900 lb



Approved for Production

Project: _____ Date: _____

Quantity: _____ By: _____

BARGER
PRECAST

C.R. Barger & Sons, Inc.
P.O. Box 370 - Kingston TN 37763
Phone 888.882.5860 - BargerAndSons.com

Specifications

Concrete: 5,000 psi minimum 28 day compressive strength
Reinforcing: Per ASTM C478 with design calculations performed by a Licensed P.E. Minimum 2" cover of all reinforcing steel.
Pipe Penetrations: All pipe penetrations are placed according to job requirements.
Pipe Seals: All pipe boots will meet ASTM C 923.
Sealant: Sealant used will meet ASTM C 990.
Steps: On 16" centers unless otherwise specified.
Preformed Invert: As required by plans or governing specifications.

72" i.d. precast concrete manhole pieces
ASTM C-478 Compliant

Date: 4.192010 Drawn By: Eric Barger Last Updated: 11.032022